

**Sliding Gate on Rail**

-

**Technical Specifications**

<b>Sliding Gates on Rail</b>		
Type	<ul style="list-style-type: none"> <li>- Single gate</li> <li>- Double gate</li> </ul>	-
Infill	<ul style="list-style-type: none"> <li>- Bars</li> <li>- Welded Mesh</li> <li>- (Full) plated</li> <li>- Chain link</li> </ul>	-
Materials	<ul style="list-style-type: none"> <li>- Steel</li> <li>- Aluminium</li> <li>- Stainless Steel</li> </ul>	-
Operation	<ul style="list-style-type: none"> <li>- Manual</li> <li>- Electromechanical</li> <li>- Hydraulic</li> </ul>	
Speed	<ul style="list-style-type: none"> <li>- 20-30 cm per sec.</li> <li>- 50 cm per sec.</li> </ul>	Slow (Basic security level) Quick (Medium security level)
Construction	<ul style="list-style-type: none"> <li>- Modular</li> <li>- Pre-assembled</li> </ul>	
Conservation of Materials	Type of antirust surface treatment :  <ul style="list-style-type: none"> <li>- Galvanized</li> <li>- Painted</li> <li>- Powder coated</li> <li>- Anodized</li> </ul>	
Standard Dimensions*  *(Can be made as a special application in other dimensions)	<ul style="list-style-type: none"> <li>- Diameter</li> <li>- Turning Circle ...</li> <li>- Height: 1 m – 2.5 m</li> <li>- Product's footprint: 7.7 – 28.1m</li> <li>- Free passage: 3 - 13 m</li> <li>- Sliding dimensions</li> </ul>	